



## Tadiran T19P

### Entry Level IP Phone

The T19P is one of Tadiran's latest answers for the entry-level IP phone that offers features and performance normally associated with much more advanced phones. The quite intentional choice of high-quality materials, combined with a generously large 132 x 64-pixel graphical LCD that gives a clear 5-line display, guarantees both a smoother user experience and easy access to much more visual information at a glance. Dual 10/100 Mbps network ports with integrated PoE are ideal for extended network use. The SIP-T19P supports a single VoIP account, simple, flexible and secure installation options, plus IPv6 and SRTP/ HTTPS/ TLS, VLAN and QoS. It includes headset use, is wall-mountable and has been designed very specifically for better business communications.

#### Highlights:

- 132 x 64-pixel graphical LCD
- Single VoIP account
- Two-port 10/100 Ethernet Switch, integrated PoE
- Full-duplex speakerphone
- Headset, wall mountable
- XML remote phonebook
- Support of Aeonix automatic provisioning mechanism
- Multi Language Support
- Extended SIP Functionality (ESF) provided by Aeonix

#### Features:

- 1 VoIP account
- Call hold, mute, DND
- One-touch speed dial, hotline
- Redial, call return, auto answer
- Call forward, call waiting, call transfer
- Group listening, SMS
- Local 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Keypad lock, emergency call
- Set date time manually or automatically
- Dial Plan, XML Browser, action URL&action URI

#### Codecs and Voice Features:

- Full-duplex hands-free speakerphone with AEC
- Codecs: G.711(A/μ), G.723, G.729AB, G.726
- DTMF: In-band, out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, AEC, PLC, AJB, AGC

#### Management:

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deployment
- Auto-provision with PnP
- Provisioning server redundancy supported
- Reset to factory, reboot
- Package tracing export, systemlog

#### Additional Features:

- Anonymous call, anonymous call rejection
- Message waiting indicator (MWI)
- Voice mail, call park, call pickup
- Intercom, paging, music on hold
- Call completion, hot-desking

#### Network and Security Features:

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv6
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- IEEE802.1X



#### Physical Features:

- 2xRJ45 10/100M Ethernet ports
- 29 keys including 4 soft keys
- 1xRJ9 handset port
- 1xRJ9 headset port
- Wall mountable
- Power adapter (optional):  
AC 100~240V input and DC 5V/600mA Output
- Power over Ethernet (IEEE 802.3af)
- Power consumption (PSU): 1.24-2.62W
- Dimensions (W\*D\*H\*T): 185MM\*188MM\*143MM\*38MM
- Operating humidity: 10~95%
- Operating temperature: -10~50°C



#### About Tadiran:

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), Contact Center, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, IP PBXs, soft switches, contact centers, Dispatch Console, IP phones and mobility and desktop solutions.

#### Visit us at: [www.tadirantele.com](http://www.tadirantele.com)

Copyright © 2015 Tadiran Telecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.